

1. Unique identification of the product
CF 12

Index a

2. Product number
562203

3. Intended use of the product according to EN 14509
Internal and external wall

4. Manufacturer identification
PANELCO SAS
Route de Chaveyriat
B.P. 10
01540 Vonnas

5. Attestation of conformity system
3

6. The notified body
???
realized reaction to fire tests and delivered the reaction to fire classification report
???

7. Declared performance

Essential characteristics and performance			European Standard
Panel and faces	Thickness of panel	120 mm	EN 14509
	Thickness of external face	0.6 mm	
	Thickness of internal face	0.6 mm	
	Mass of the product	29.41 kg/m ²	
Steel	Tensile strength of external face	S280GD	
	Tensile strength of internal face	S280GD	
Core	Core	Mineral wool	
	Density of core material	165 kg/m ³	
Durability	Durability	NPD	
	Cross panel tensile strength	0.018 MPa	
Mechanical resistance	Shear strength	0.025 MPa	
	Shear modulus	3 MPa	
	Shear strength after long-term loading (100 000 h)	-	
	Compressive strength	0.05 MPa	
	Creap coefficient t= 2000 h	-	
	Creap coefficient t= 100 000 h	-	
	Bending moment capacity (+) in span	3.16 kN.m/m	
	Bending moment capacity (+) in span - high temperature	3.16 kN.m/m	
	Bending moment capacity (-) in span	3.16 kN.m/m	
	Bending moment capacity (-) in span - high temperature	3.16 kN.m/m	
	Bending moment capacity (+) over a central support	-	
	Bending moment capacity (+) over a central support - high temperature	-	
	Bending moment capacity (-) over a central support	-	
	Bending moment capacity (-) over a central support - high temperature	-	
	Wrinkling strength of the external face in span	36.8 MPa	
	Wrinkling strength of the external face in span - high temperature	36.8 MPa	
	Wrinkling strength of the external face over a central support	-	
	Wrinkling strength of the external face over a central support - high temperature	-	
	Wrinkling strength of the internal face in span	36.8 MPa	
	Wrinkling strength of the internal face over a central support	-	
Accessibility	-		
Thermal insulation performance	Thermal conductivity of the core	0.041 W/(m.K)	
	Thermal transmittance	0.326 W/(m ² .K)	
Fire	Reaction to fire	A2-s1-d0	Report n° ???
	Fire resistance	See PV RS05-010	
Permeability	Air permeability	NPD	EN 14509
	Water permeability	NPD	
	Water vapour permeability	NPD	
Acoustic	Airborne sound insulation	NPD	
	Sound absorption	NPD	
Dimensional tolerances	Dimensional tolerances	NPD	
	Substances of very high concern according to REACH	No	REACH
Environnement	Regulated hazardous substances emission	(a)	EN 14509

(a) Faces in contact with the interior air shall not emit regulated hazardous substances exceeding the maximum permitted levels specified in the European or national regulations. European test methods are being developed. An informative database of European and national provisions relating to controlled substances can be found on the EUROPA website, accessible at the following address:

http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Vonnas, 17/07/2018

Mr. Bruno Curial

